







AMERICAN REACH IN CHILLER AND FREEZER

Product Photo						
Model Number	UR-27C-1G	UR-27F-1G	UR-54C-2G	UR-54F-2G	UR-78C-3G	UR-78F-3G
Unit Size (mm) [WxDxH]	700x825x2095 (27.5"x32.5"x82.5")		1370x825x2095 (54"x32.5"x82.5")		2020x825x2095 (80"x32.5"x82.5")	
Net Capacity (L)	430 (15.2cu.ft)		920 (32.5cu.ft)		1420 (50.2cu.ft)	
Temperature Range (°C)	0~10 (32~50°F)	-22~-18 (-8~0°F)	0~10 (32~50°F)	-22~-18 (-8~0°F)	0~10 (32~50°F)	-22~-18 (-8~0°F)
Climatic Class	4 (32°C & 55% R.H)					
Voltage	110V/60Hz					
Controller Type	Digital					
Body Material	AISI 430					
Body Thickness (mm)	75					
Isolation	Cyclopentane (40kg/m ³)					
Drawer Quantity (Pc)	1		2		3	
Chamber Quantity (Pc)	1					
Shelf Quantity (Pc)	4 (530x650mm 20.9"x25.6")		8 (530x650mm 20.9"x25.6")		12 (530x650mm 20.9"x25.6")	
Cooling Mode	Forced air					
Defrosting Mode	Electric heater					
Rated Power (W)	300	700	350	1375	850	1830
Compressor (HP)	1/6	3/4	1/5	3/4*2	1/2	1*2
Energy Consumption (Kwh/24H)	3.6	11.0	4.2	23.0	8.0	30.0
Energy Class	/	/	/	/	/	/
Refrigerant	R-290					
Customized Items	Voltage/Body material/Digital controller/Feet					