









BLAST CHILLER AND FREEZER (STANDARD)

Product Photo								
Model Number	BCF12	BCF20	BCF25	BCF35	BCF45	BCF65	BCF90	BCF130
Unit Size (mm) [WxDxH]	710x700x560	800x800x850	800x800x1000	800x800x1150	800x800x1385	800x800x1920	1560x800x1385	1560x800x1920
Tray Quantity (Pc) [GN1/1 & 60x40]	3	4	5	7	10	15	20	30
Net Capacity (L)	55	90	110	155	210	305	210*2	310*2
Temperature Range (°C)	-35	-40						
Chilling Capacity (Kg)	12	20	25	35	50	75	100	150
Chilling Time (Mins) [75°C → 3°C]	90							
Freezing Capacity (Kg)	6	10	12.5	17.5	25	37.5	50	75
Freezing Time (Mins) [75°C → -18°C]	240							
Climatic Class	4 (32°C & 55% R.H)							
Voltage	220~240V/50Hz							
Controller Type	Touch button with LCD display & food core probe							
Body Material	AISI 304							
Body Thickness (mm)	60	85						
Isolation	Cyclopentane (40kg/m ³)							
Door Quantity (Pc)	1						2	2
Chamber Quantity (Pc)	1						2	2
Tray Distance (mm)	75							
Cooling Mode	Forced air							
Defrosting Mode	Electrical heater							
Rated Power (W)	650	1100	1100	1100	1250	1800	2500	3600
Compressor (HP)	3/4	1 1/4	1 1/4	1 1/4	1 1/2	2	1 1/2*2	2*2
Energy Consumption (Kwh/24H)	/	/	/	/	/	/	/	/
Refrigerant	R404A							
Customized Items	Voltage/Body material/Digital controller/Tray bracket/Feet							