















## GLASS DOOR CHILLER AND FREEZER (CLASSIC)

| Product Photo                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------------------------------------|---|---|---|---|---|---|---|---|---|--|---|---|---|---|--|
| <b>Model Number</b>                   | SG160L1F  | SG240L1F  | SG380L1F  | SG700L2F  | SD160L1F  | SD240L1F  | SD380L1F  | SD700L2F  | SG468L1F  | SG958L2F   | SG1210L3F   | SD468L1F  | SD958L2F  | SD1210L3F   |  |
| <b>Unit Size (mm) [WxDxH]</b>         | 405x430x1950  | 550x580x2000  | 650x720x2000  | 1200x720x2000   | 405x430x1950  | 550x580x2000  | 650x720x2000  | 1200x720x2000   | 686x760x2130  | 1370x760x2130  | 1830x760x2130   | 686x760x2130  | 1370x760x2130   | 1830x760x2130   |  |
| <b>Net Capacity (L)</b>               | 160   | 240   | 380   | 700   | 160   | 240   | 380   | 700   | 468   | 958  | 1210  | 468   | 958   | 1210  |  |
| <b>Temperature Range (°C)</b>         | 0~10  |   |   |   | -22~-18   |   |   |   | 0~10  |  |   |   | -22~-18   |   |  |
| <b>Climatic Class</b>                 | 4 (32°C & 55% R.H)  |   |   |   |   |   |   |   | 4 (32°C & 55% R.H)  |  |   |   |   |   |  |
| <b>Voltage</b>                        | 220~240V/50Hz   |   |   |   |   |   |   |   | 220~240V/50Hz   |  |   |   |   |   |  |
| <b>Controller Type</b>                | Digital   |   |   |   |   |   |   |   | Digital   |  |   |   |   |   |  |
| <b>Body Material</b>                  | Coated steel  |   |   |   |   |   |   |   | Coated steel  |  |   |   |   |   |  |
| <b>Body Thickness (mm)</b>            | 65  |   |   |   |   |   |   |   | 65  |  |   |   |   |   |  |
| <b>Isolation</b>                      | Cyclopentane(40kg/m³)   |   |   |   |   |   |   |   | 40kg/m³   |  |   |   |   |   |  |
| <b>Door Quantity (Pc)</b>             | 1   | 1   | 1   | 2   | 1   | 1   | 1   | 2   | 1   | 2  | 3   | 1   | 2   | 3   |  |
| <b>Chamber Quantity (Pc)</b>          | 1   |   |   |   |   |   |   |   |   |  |   |   |   |   |  |
| <b>Shelf Quantity (Pc) [EN 60x40]</b> | 4   | 5   | 5   | 10  | 4   | 5   | 5   | 10  | 5   | 10   | 15  | 5   | 10  | 15  |  |
| <b>Cooling Mode</b>                   | Forced air  |   |   |   |   |   |   |   | Forced air  |  |   |   |   |   |  |
| <b>Defrosting Mode</b>                | Electric heater   |   |   |   |   |   |   |   | Electric heater   |  |   |   |   |   |  |
| <b>Rated Power (W)</b>                | 280   | 320   | 320   | 430   | 350   | 500   | 680   | 1300  | 320   | 550  | 850   | 700   | 1375  | 1830  |  |
| <b>Compressor (HP)</b>                | 1/8   | 1/6   | 1/6   | 1/4   | 1/3   | 1/2   | 3/4   | 3/4*2   | 1/6   | 1/4  | 1/2   | 3/4   | 3/4*2   | 1*2   |  |
| <b>Energy Consumption (Kwh/24H)</b>   | 3.3   | 3.8   | 3.8   | 5.2   | 6.0   | 9.0   | 11.0  | 22.0  | 3.8   | 6.5  | 10.2  | 11.0  | 23.0  | 30.0  |  |
| <b>Energy Class</b>                   | /   | /   | /   | /   | /   | /   | /   | /   | /   | /  | /   | /   | /   | /   |  |
| <b>Refrigerant</b>                    | R-290   |   |   |   |   |   |   |   | R-290   |  |   |   |   |   |  |
| <b>Customized Items</b>               | Voltage/Body material/Shelf material/Digital controller                           |   |   |   |   |   |   |   | Voltage/Body material/Shelf material/Digital controller                           |  |   |   |   |   |  |