



















ASIAN REACH IN CHILLER AND FREEZER (SNACK)

Product Photo																		
Model Number	CFD1-C1	CFD1-F1	CFD1-C2	CFD1-F2	CFD2-C2	CFD2-F2	CFD2-C4	CFD2-F4	CFD3-C3	CFD3-F3	CFD3-C6	CFD3-F6	CFD1-C1-G	CFD1-F1-G	CFD2-C2-G	CFD2-F2-G	CFD3-C3-G	CFD3-F3-G
Unit Size (mm) [WxDxH]	700x730x2100 (27.5"x28.7"x82.7")		700x730x2100 (27.5"x28.7"x82.7")		1400x730x2100 (55.1"x28.7"x82.7")		1400x730x2100 (55.1"x28.7"x82.7")		2100x730x2100 (82.7"x28.7"x82.7")		2100x730x2100 (82.7"x28.7"x82.7")		700x730x2100 (27.5"x28.7"x82.7")		1400x730x2100 (55.1"x28.7"x82.7")		2100x730x2100 (82.7"x28.7"x82.7")	
Net Capacity (L)	420 (14.5cu.ft)		420 (14.5cu.ft)		950 (33.6cu.ft)		950 (33.6cu.ft)		1480 (52.3cu.ft)		1480 (52.3cu.ft)		420 (14.5cu.ft)		950 (33.6cu.ft)		1480 (52.3cu.ft)	
Temperature Range (°C)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)	0~-10 (32~50°F)	-22~-18 (-8~0°F)
Climatic Class	5 (43°C & 80% R.H)												32 (90°F)					
Voltage	220V/50Hz												110V/60Hz					
Controller Type	Digital												Digital					
Body Material	AISI 201												AISI 201					
Body Thickness (mm)	60												60					
Isolation	Cyclopentane (40kg/m³)												40kg/m³					
Door Quantity (Pc)	1		2		2		4		2		4		1		2		2	
Chamber Quantity (Pc)	1												1					
Shelf Quantity (Pc)	4 (570x600mm 22.4"x23.6")		4 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")		4 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")		8 (570x600mm 22.4"x23.6")	
Cooling Mode	Forced air												Forced air / Air forcé / دفع الهواء					
Defrosting Mode	Electric heater												Electrical heater / Chauffage électrique / سخان كهربائي					
Rated Power (W)	300	500	300	500	350	980	350	980	850	1400	850	1400	300	700	350	1375	850	1830
Compressor (HP)	1/6	1/2	1/6	1/2	1/5	1	1/5	1	1/2	3/4*2	1/2	3/4*2	1/6	3/4	1/5	3/4*2	1/2	1*2
Energy Consumption (kwh/24h)	3.6	8.0	3.6	8.0	4.2	16.0	4.2	16.0	8.0	23.0	8.0	23.0	3.6	11.0	4.2	23.0	8.0	30.0
Energy Class	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/	/
Refrigerant	R-290												R-290					
Customized Items	Voltage/Body material/Shelf material/Digital controller/Wheel												Voltage/Body material/Shelf material/Digital controller/Wheel					