









## RETARDER PROOFER

<b>Product Photo</b>								
<b>Model Number</b>	XFL1-16C	XFL1-16D	XFL2-32C	XFL2-32D	XFL1-18C	XFL1-18D	XFL1-36C	XFL1-36D
<b>Unit Size (mm) [WxDxH]</b>	700x850x1980		1220x850x1980		700x850x2100		800x1050x2100	
<b>Net Capacity (L)</b>	520		990		695		1020	
<b>Temperature Range (°C)</b>	0~40	-22~40	0~40	-22~40	0~40	-22~40	0~40	-22~40
<b>Relative Humidity (%)</b>	40~90				40~90			
<b>Climatic Class</b>	5 (43°C & 80% R.H)				5 (43°C & 80% R.H)			
<b>Voltage</b>	220~240V/50Hz				220~240V/50Hz			
<b>Controller Type</b>	Digital				Digital			
<b>Body Material</b>	AISI 201				AISI 201			
<b>Body Thickness (mm)</b>	60				60			
<b>Isolation</b>	Cyclopentane (40kg/m³)				Cyclopentane (40kg/m³)			
<b>Door Quantity (Pc)</b>	1	2		1		1		
<b>Chamber Quantity (Pc)</b>	1				1			
<b>Shelf Quantity (Pc) [EN 60x40]</b>	16	32		18		36		
<b>Cooling Mode</b>	Forced air				Forced air			
<b>Defrosting Mode</b>	Forced air				Forced air			
<b>Rated Power (W)</b>	300	500	350	980	300	500	350	800
<b>Compressor (HP)</b>	1/6	1/2	1/5	1	1/6	1/2	1/5	3/4
<b>Energy Consumption (Kwh/24H)</b>	3.6	8	4.2	16	3.6	8	4.2	14
<b>Energy Class</b>	/	/	/	/	/	/	/	/
<b>Refrigerant</b>	R-290				R-290			
<b>Customized Items</b>	Voltage/Body material/Digital controller/Glass door/Wheel				Voltage/Body material/Digital controller/Glass door/Wheel			