









## BAKERY REACH-IN CHILLER AND FREEZER

<b>Product Photo</b>								
<b>Model Number</b>	BG0.6L1F	BD0.6L1F	BG1.2L2F	BD1.2L2F	BG0.7L1F	BD0.7L1F	BG1.3L2F	BD1.3L2F
<b>Unit Size (mm) [WxDxH]</b>	700x800x1980		1220x800x1980		700x940x1980		1220x940x1980	
<b>Net Capacity (L)</b>	550		1050		660		1260	
<b>Temperature Range (°C)</b>	0~10	-22~-18	0~10	-22~-18	0~10	-22~-18	0~10	-22~-18
<b>Climatic Class</b>	5 (43°C & 80% R.H)				5 (43°C & 80% R.H)			
<b>Voltage</b>	220~240V/50Hz				220~240V/50Hz			
<b>Controller Type</b>	Digital				Digital			
<b>Body Material</b>	AISI 201				AISI 201			
<b>Body Thickness (mm)</b>	60				60			
<b>Isolation</b>	Cyclopentane (40kg/m <sup>3</sup> )				Cyclopentane (40kg/m <sup>3</sup> )			
<b>Door Quantity (Pc)</b>	1		2		1		2	
<b>Chamber Quantity (Pc)</b>	1				1			
<b>Shelf Quantity (Pc) [EN 60x40]</b>	14		28		14 (460x740mm)		28 (460x740mm)	
<b>Cooling Mode</b>	Forced air				Forced air			
<b>Defrosting Mode</b>	Electric heater				Electric heater			
<b>Rated Power (W)</b>	300	500	350	980	300	500	350	980
<b>Compressor (HP)</b>	1/6	1/2	1/5	1	1/6	1/2	1/5	1
<b>Energy Consumption (Kwh/24H)</b>	3.6	8.0	4.2	16.0	3.6	8.0	4.2	16.0
<b>Energy Class</b>	/	/	/	/	/	/	/	/
<b>Refrigerant</b>	R-290				R-290			
<b>Customized Items</b>	Voltage/Body material/Digital controller/Glass door/Wheel				Voltage/Body material/Digital controller/Glass door/Wheel			