








GN REACH-IN CHILLER AND FREEZER (ECO LINE)

| | | | | | | | |
|-------------------------------------|---|---|---|---|--|---|---|
| Product Photo |  |  |  |  |  |  |  |
| Model Number | GN550TN | GN550BT | GN1200TN2 | GN1200BT2 | GN1200TN/TN | GN1200TN/BT | GN1200BT/BT |
| Unit Size (mm) [WxDxH] | 700x830x2050 | | 1370x830x2050 | | | | |
| Net Capacity (L) | 570 | | 1280 | | 570/570 | | |
| Temperature Range (°C) | 0~10 | -22~-18 | 0~10 | -22~-18 | 0~10 / 0~10 | 0~10 / -22~-18 | -22~-18 / 22~-18 |
| Climatic Class | 5 (43°C & 80% R.H) | | | | | | |
| Voltage | 220~240V/50Hz | | | | | | |
| Controller Type | Digital | | | | | | |
| Body Material | AISI 201 | | | | | | |
| Body Thickness (mm) | 80 | | | | | | |
| Isolation | Cyclopentane (40kg/m ³) | | | | | | |
| Door Quantity (Pc) | 1 | | 2 | | | | |
| Chamber Quantity (Pc) | 1 | | | | 2 | | |
| Shelf Quantity (Pc) [GN2/1] | 4 | | 8 | | | | |
| Cooling Mode | Forced air | | | | | | |
| Defrosting Mode | Hot gas | | | | | | |
| Rated Power (W) | 110 | 330 | 240 | 590 | 220 | 440 | 660 |
| Compressor (HP) | 1/6 | 1/3 | 1/4 | 3/4 | 1/6*2 | 1/6+1/3 | 1/3*2 |
| Energy Consumption (Kwh/24H) | 1.2 | 6.6 | 2.0 | 11.0 | 2.4 | 7.8 | 13.2 |
| Energy Class | A | C | C | D | A | D | C |
| Refrigerant | R600a | R290 | R290 | R290 | R600 | R600a & R290 | R290 |
| Customized Items | Voltage/Body material/Shelf material/Digital controller/Glass door/Wheel | | | | | | |