










## ASIAN REACH-IN CHILLER AND FREEZER (LUXURY)

<b>Product Photo</b>									
<b>Model Number</b>	G0.5HL2F	D0.5HL2F	QD0.5HL2F	G1.0HL4F	D1.0HL4F	QD1.0HL4F	G1.6HL6F	D1.6HL6F	QD1.6HL6F
<b>Unit Size (mm) [WxDxH]</b>	620x(760+50)x1980			1220x760+50x1980			1837x760+50x1980		
<b>Net Capacity (L)</b>	450		205/205	980		450/450	1530		980/450
<b>Temperature Range (°C)</b>	-5~10	-20~-5	-5~10/-20~-5	-5~10	-20~-5	-5~10/-20~-5	-5~10	-20~-5	-5~10/-20~-5
<b>Climatic Class</b>	4 (38°C & 55% R.H)								
<b>Voltage</b>	220~240V/50Hz								
<b>Controller Type</b>	Digital								
<b>Body Material</b>	AISI 201								
<b>Body Thickness (mm)</b>	60								
<b>Isolation</b>	Cyclopentane (40kg/m <sup>3</sup> )								
<b>Door Quantity (Pc)</b>	2	2	2	4	4	4	6	6	6
<b>Chamber Quantity (Pc)</b>	1		2	1	1	2	1	1	2
<b>Shelf Quantity (Pc)</b>	3 (480x570)			6 (530x570)			9 (550x570)		
<b>Cooling Mode</b>	Forced air								
<b>Defrosting Mode</b>	Hot gas								
<b>Rated Power (W)</b>	170	320	320	280	470	450	490	750	600
<b>Compressor (HP)</b>	1/4	1/3	1/3	1/2	1	1/4+1/2	1/4+1/3	1/2+1	1/3+1/2
<b>Energy Consumption (Kwh/24H)</b>	1.3	5.1	5.1	2.9	7.5	4.2	6.4	10.5	8.1
<b>Energy Class</b>	/	/	/	/	/	/	/	/	/
<b>Refrigerant</b>	R-290								
<b>Customized Items</b>	Voltage/Body material/Shelf material/Digital controller/Big door/Glass door/Wheel								