









AMERICAN UNDER COUNTER

Product Photo								
Model Number	UC-27C-1	UC-27F-1	UC-48C-2	UC-48F-2	UC-60C-2	UC-60F-2	UC-72C-3	UC-72F-3
Unit Size (mm) [WxDxH]	686x760x900 (27"x30"x35.4")		1220x760x900 (48"x30"x35.4")		1520x760x900 (60"x30"x35.4")		1830x760x900 (72"x30"x35.4")	
Net Capacity (L)	130 (4.6cu.ft)		230 (8.1cu.ft)		320 (11.3cu.ft)		380 (13.4cu.ft)	
Temperature Range (°C)	0~10 (32~50°F)	-22~-18 (-8~0°F)	0~10 (32~50°F)	-22~-18 (-8~0°F)	0~10 (32~50°F)	-22~-18 (-8~0°F)	0~10 (32~50°F)	-22~-18 (-8~0°F)
Climatic Class	4 (32°C & 55% R.H)							
Voltage	110V/60Hz							
Controller Type	Digital							
Body Material	AISI 430							
Body Thickness (mm)	60							
Isolation	Cyclopentane (40kg/m ³)							
Drawer Quantity (Pc)	1		2		2		3	
Chamber Quantity (Pc)	1							
Shelf Quantity (Pc)	2 (570x485mm 22.4"x19")		4 (545x485mm 21.5"x19")		4 (700x485mm 27.6"x19")		6 (545x485mm 21.5"x19")	
Cooling Mode	Forced air							
Defrosting Mode	Electric heater							
Rated Power (W)	280	450	350	500	350	500	350	500
Compressor (HP)	1/6	3/8	1/5	1/2	1/5	1/2	1/5	1/2
Energy Consumption (Kwh/24H)	3.0	7.0	4.0	8.0	4.0	8.0	4.0	8.0
Energy Class	/	/	/	/	/	/	/	/
Refrigerant	R-290							
Customized Items	Voltage/Body material/Drawers/Glass door/Digital controller/Wheel							