









BACK BAR (VENTILATION)

Product Photo								
Model Number	SG160	SG250	SG380	SG520	SD160	SD250	SD380	SD520
Unit Size (mm) [WxDxH]	550x520x850	920x520x850	1350x520x850	1800x520x850	550x520x850	920x520x850	1350x520x850	1800x520x850
Net Capacity (L)	100	180	290	360	100	180	290	360
Temperature Range (°C)	0~10				0~-18			
Climatic Class	4 (32°C & 55% R.H)				4 (32°C & 55% R.H)			
Voltage	220~240V/50Hz				220~240V/50Hz			
Controller Type	Digital				Digital			
Body Material	AISI 201				AISI 201			
Body Thickness (mm)	50				60			
Isolation	Cyclopentane (40kg/m ³)				Cyclopentane (40kg/m ³)			
Door Quantity (Pc)	1	2	3	4	1	2	3	4
Chamber Quantity (Pc)	1				1			
Shelf Quantity (Pc)	2	4	6	8	2	4	6	8
Cooling Mode	Forced air				Forced air			
Defrosting Mode	Auto				Auto			
Rated Power (W)	200	200	200	230	250	300	350	430
Compressor (HP)	1/8	1/8	1/8	1/6	1/4	1/3	1/2	3/4
Energy Consumption (Kwh/24H)	2.0	2.0	3.0	4.0	4.8	5.8	6.7	8.3
Energy Class	/	/	/	/	/	/	/	/
Refrigerant	R600a				R-290			
Customized Items	Voltage/Body material/Shelf material/Digital controller/Solid door				Voltage/Body material/Shelf material/Digital controller/Solid door			